

Granville Hypalube LX Mineral 10W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville Hypalube LX 10W/30 is a superior mineral engine oil, formulated to increase engine protection during cold start up thereby reducing engine wear. Hypalube 10W/30 is a low viscosity engine oil that offers improved fuel economy and outstanding engine cleanliness.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SL/CF
ACEA: A2/B2 & E2
MB: 229.1
VW: 505.00
Ford: WSS-M2C909-A

PRODUCT BENEFITS

- * Ensures lubricant performance
- * Excellent high & low temperature performance
- * Suitable for petrol and diesel engines
- * Outstanding engine cleanliness and sludge control

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0083	5020618000839
5 Litre	0081	5020618000815
20 Litre	0091	5020618000914
199 Litre	0094	5020618000945



Granville Hypalube LX Mineral 10W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.9
Cold Cranking Viscosity	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		12.12
Pour Point	ASTM D97	°C		-30	-33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		13	
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			69.24
Density	ASTM D792	@ 15°C			0.869
Viscosity Index	ASTM D2270				147.777

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

