

Granville Hypalube C4 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville Hypalube C4 5W/30 is an advanced, fully synthetic low viscosity engine oil formulated to meet the performance demands required by manufacturers who recommend an oil that combines high performance, fuel efficiency and emission control. Manufactured to a Low SAPS (Sulphated ash, phosphorous and sulphur content) formulation. Recommended for all engine types where the manufacturer specifies a C4 oil.

It is imperative that the correct oil is used as costly repairs will be required if the wrong specification of lubricant is used.



* Image for illustrative purposes only.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C4
MB: 226.51
Renault: RN0720

SIZE	PART NO	BARCODE
1 Litre	0814	5020618008149
5 Litre	0815	5020618008156
20 Litre	0819	5020618008194
199 Litre	0818	5020618008187

PRODUCT BENEFITS

- * Low SAPS (Sulphated ash, phosphorous and sulphur content) formulation
- * Fully Synthetic

PRODUCT USAGE

Use where recommended by the engine manufacturer

DIRECTIONS FOR USE

Use as required by the engine manufacturer

STORAGE INSTRUCTIONS

Store sealed and pright in a cool dry place out of the reach of children



Granville Hypalube C4 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	11.572
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.46
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		11	
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			71.05
Density	ASTM D792	@ 15°C			0.851

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

