

Veedol Multigrade Super 10W/40

1 Litre & 5 Litre

PRODUCT DESCRIPTION

Veedol Multigrade Super 10W-40 motor oil is based on a combination of high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained: high and stable viscosity index; fast cold start; strong resistance against oxidation; good detergency and dispersion; safe lubrication film at high temperatures; protection against wear, corrosion and foaming. Veedol Multigrade Super 10W-40 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

OEM APPROVALS

MB-Approval: 229.1

RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: A3/B4
API: SL/CF
VW: 502.00 & 505.00



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	5020	5020618050209
5 Litre	5021	5020618050216

PRODUCT BENEFITS

- * OEM Approved product
- * Good detergency and dispersion
- * Strong protection against wear, corrosion and foaming

PRODUCT USAGE

Recommended for applications where this grade and specification of lubricant is required

DIRECTIONS FOR USE

Use as per the engine manufacturers handbook



Veedol Multigrade Super 10W/40

1 Litre & 5 Litre

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber oily liquid
Odour	: Characteristic
Specific Gravity	: 0.873
Solubility	: Insoluble in water

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

